

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF  
WARNING: POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirement.

## Installation Steps.

1. Carefully unpack your new fixture, take the inner shade and diffuser out of the 8-618 carton, take the outer housing and inner reflector out of the 8-2018-XXXX carton,
2. Attach the mounting plate (A) to the outlet box using 2 outlet box screws (C).
3. Select desired CCT: 2700k, 3000K, 4000K, 5000K, 6500K on the CCT switch located in the inner shade
4. Make wire connections:
  - Attach the ground wire to house ground wire using a wire nut.
  - (Or attach them to the mounting plate (A) with a green ground screw.
  - Attach white wire from light to white wire from power source with a wire nut.
  - Attach black wire from light to black wire from power source with a wire nut.
5. Attach the inner shade to mounting plate (A) by using decorative nut (E).
6. Pull diffuser and outer housing to the inner reflector, Together them to a group (Fig. 2)
7. Twist the group in a clockwise direction to secure to inner shade (D). Double check the holder bar into the key hole (Fig. 3)
8. Turn on the power.

